MTP / MPO Fiber Optic Loopback Tester (Multimode 50/125um, OM3) - Female

MODEL NUMBER: **N844-LOOP-12F**

Highlights

- MTP / MPO Loopback for 40GbE QSFP+ Optical Testing
- 50/125 OM3 6-Fiber

System Requirements

- Networking hardware with MTP / MPO ports

Package Includes

- MTP / MPO Fiber Optic Loopback Tester (Multimode 50/125um, OM3) - Female

Description

Tripp Lite N844-LOOP-12F MTP / MPO OM3 Fiber Optic Loopback Tester is typically used for test and measurement procedures in networking environments.The device is ideal for a multitude of applications that require signal looping in a MTP / MPO form factor. Features push-pull tab for easy disconnect. A dust cap is included for protection during storage.

Features

- MTP / MPO OM3 Loopback Tester
- Push-pull tab for quick disconnect
- Protective dust cover included for protection during storage
- 4-inch overall length
- Pin config: 1 -12, 2-11, 3-10, 4-9, 5-8, 6-7

Specifications

OVERVIEW	
UPC Code	037332188205
Attenuation @ 1300NM	0.7dB/Km
Attenuation @ 850NM	2.5dB/Km
Accessories Type	Cable Tester
Technology	Multimode(All versions); MTP/MPO
Optical Mode	OM3

INPUT	
Cable Length (ft.)	0.7
Cable Length (m)	0.2
Cable Length (in.)	4
Cable Length (cm)	10.16

PHYSICAL	
Shipping Dimensions (hwd / in.)	5.900 x 4.000 x 0.500
Shipping Dimensions (hwd / cm)	14.99 x 10.16 x 1.27
Shipping Weight (lbs.)	0.0130
Shipping Weight (kg)	0.01
Color	Aqua

ENVIRONMENTAL	
Operating Temperature Range	-4 TO 140 F (-20 TO 60 C)
Storage Temperature Range	-4 TO 140 F (-20 TO 60 C)

CONNECTIONS	
Side A - Connector 1	12-STRAND MTP (FEMALE)

WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty