



NOTES:

MATERIALS:
 MOLDED BODY: BLACK PVC
 COUPLERS: STAINLESS STEEL OR NI PLATED BRASS
 CONTACTS: GOLD/NICKEL OVER COPPER ALLOY
 MC INSERTS: BLACK PVC
 FRICTION RINGS(MC FEM.): NYLON

ELECTRICAL:
 CURRENT RATING: 7AMP MAX
 VOLTAGE RATING: 300V

MECHANICAL:
 TEMPERATURE RANGE: -20° TO 60°C
 INGRESS PROTECTION: IP 67

AGENCY CERTIFICATIONS:
 AGENCY: CSA PENDING

PART NUMBER REFERENCE:

| MATERIAL NUMBER | ENGINEERING NUMBER | COUPLER STYLE | GAUGE |
|-----------------|--------------------|---------------------------|-------|
| 1300450002 | T140140-001FF8 | HEX - 316 STAINLESS STEEL | 18AWG |
| 1300450001 | T140140-001FF | KNURLED - NI PLATED BRASS | 18AWG |

| | | | | | | | | | | | |
|---|--------------------|---|--|--------------------------------|---------------------------|---------------------------|--------------------------------------|-------------------------------|---|--|--|
| UPDATE PER JM EC NO: WNA2009-0313 DRWN: LHARTMAN 2008/10/27 CH'KD: VOU 2008/11/07 APPR: JFMURPHY 2008/11/10 | DESCRIPTION REV | QUALITY SYMBOL | GENERAL TOLERANCES (UNLESS SPECIFIED) | | DIMENSION STYLE | SCALE | DESIGN UNITS | THIRD ANGLE PROJECTION | | | |
| | | ▽=0 C=0 | mm INCH | ---- | ---- | ---- | 2:1 | INCH | TITLE MINI-CHANGE TEE 4 POLE MA/FE W/FE DROP | | |
| | | 4 PLACES ±---- ±---- 3 PLACES ±---- ±---- 2 PLACES ±---- ±---- 1 PLACE ±---- ±---- | ANGULAR ±1/2° | DRAWN BY LHARTMAN | DATE 2008/10/27 | CHECKED BY VOU | DATE 2008/10/27 | MOLEX INCORPORATED | | | |
| | | DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | SEE TABLE | APPROVED BY JFMURPHY | DATE 2008/10/27 | MATERIAL NO. SEE TABLE | DOCUMENT NO. SD-130045-001 | SHEET NO. 1 OF 1 | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | |
| | | C | REV | | | | | | | | |