








APPLICABLE STANDARD			
RATING	OPERATING TEMPERATURE RANGE	 -55 °C TO +85 °C	STORAGE TEMPERATURE RANGE   -55 °C TO +85 °C
	VOLTAGE		CURRENT
SPECIFICATIONS			
ITEM	TEST METHOD	REQUIREMENTS	QT AT
CONSTRUCTION			
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X X
MARKING	CONFIRMED VISUALLY.		X X
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED
 3	DIS-E-002197	MT. ITANO	HK. TANAKA
REMARK	PACKING MATERIAL IS NOT INCLUDED.	APPROVED	HO. MIWA
 		CHECKED	TH. KAMEYA
		DESIGNED	SS. SATOH
		DRAWN	SS. SATOH
Unless otherwise specified, refer to JIS C 5402.			
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-121484-01
HRS	SPECIFICATION SHEET	PART NO.	TM21P-88P (**)
	HIROSE ELECTRIC CO., LTD.	CODE NO.	 1/1