

## Cat6a 110-Style Punchdown RJ45 Keystone Jack, White, TAA

MODEL NUMBER: N238-001-WH-6A



Terminate your Cat6a cables at standard patch panels, surface-mount boxes or keystone wall plates.

### Description

Strengthen your high-speed network with the N238-001-WH-6A Cat6a 110-Style Punchdown RJ45 Keystone Jack. Recommended for all Cat6a cabling environments, the keystone jack with a uniquely patterned printed circuit board is designed for 650 MHz performance and complies with EIA/TIA Cat6a connecting hardware specifications. The compact white casing snaps into any conventional patch panel, outlet box or wall plate. Dual-color-coded labeling is present for 568A and 568B (258A) wiring schemes. The N238-001-WH-6A meets UL-certified ANSI/TIA/EIA-568-B.2-10 Cat6a Permanent Link/Channel Identification Testing standards for Cat6a cabling installations. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

### Features

#### Cat6a Keystone Jack Strengthens Your High-Speed Network

- Compact casing snaps easily into standard patch panel, outlet box or wall plate
- Recommended for all Cat6a cabling environments
- Uniquely patterned printed circuit board designed for 650 MHz performance
- Dual-color-coded labeling for 568A/B (258A) wiring schemes
- UL-certified
- Meets all EIA/TIA Cat6a requirements

#### TAA-Compliant

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

## Specifications

### Highlights

- Keystone design for use with standard data wall plate
- Dual-color-coded labeling for 568A/B (258A) wiring schemes
- Compatible with all Cat6a cables
- Meets all EIA/TIA Cat6a requirements
- TAA-compliant for GSA Schedule purchases

### Package Includes

- N238-001-WH-6A Cat6a 110-Style Punchdown RJ45 Keystone Jack, White
- Shutter/dust cap



<b>OVERVIEW</b>	
UPC Code	037332204219
Technology	Cat5/5e; Cat6; Cat6a
<b>PHYSICAL</b>	
Shipping Dimensions (hwd / in.)	0.500 x 4.000 x 5.300
Shipping Dimensions (hwd / cm)	1.27 x 10.16 x 13.46
Shipping Weight (lbs.)	0.1000
Shipping Weight (kg)	0.05
Color	Gray; White
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	14 to 140 F (-10 TO 60 C)
Storage Temperature Range	-40 to 154 F (-40 TO 68 C)
Relative Humidity	10% to 90% RH
<b>CONNECTIONS</b>	
Ports	1
Side A - Connector 1	RJ45 (FEMALE)
Side B - Connector 1	110 IDC
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>